

Key Features

- Arctic location provides access to most satellite orbits
- Right-sized station for smallsat and nanosat missions
- Accommodates major downlink frequencies for today's mission operators
- High-speed data links using Canada's newest Arctic fibre infrastructure
- Hosted at a secure Government of Canada facility
- Levelling platform adjusts for ground movement during freeze/thaw cycles, ensuring pointing stability

Benefits

- Downlink more on-board data, more often
- Major costs savings, especially for higher density constellations with large volumes of data



© C-CORE (Rev 2: Winter 2019)

Information will be updated periodically to reflect continuous improvement .

Arctic Satellite Groundstations

Summary

C-CORE's Arctic Ground Stations are an innovative solution that combines extensive downlink capabilities with strong data security and fast, reliable access. Located in Canada's Northwest Territories (Inuvik) and Labrador (Happy Valley Goose Bay), C-CORE's high-latitude ground stations are strategically positioned to support the new generation of satellites. These missions are higher density constellations, and mission operators are demanding more cost-effective solutions optimized for high volumes of smallsat receptions. C-CORE delivers.

Inuvik is an ideal location for polar-orbiting satellites, where up to 12 passes per day for each satellite can be downlinked. C-CORE joins Canadian, German and Swedish mission operators at the Inuvik Satellite Station Facility (ISSF), benefitting from its secure location developed by Natural Resources Canada, reliable high-speed fibre communications and all-season operations.

Inuvik Ground Station

- Location: Inuvik Satellite Station Facility, developed by NRCAN
- GPS Coordinates: 133W 33 0.58, 68N 19 9.12
- Commissioned in December 2017
- Environmental Specifications:
 - ✧ Temperature: -40°C to +70°C
 - ✧ Wind: 240 km/hr

Happy Valley Goose Bay

- Coming in late 2019



C-CORE's Arctic Satellite Ground Stations

Antenna Specifications

- 3.4m Carbon Fibre Reflector
- Co-polar Reflection Pattern: REC 465-5
- Prime Focus Feeds
- S-band (2.2GHz) Downlink Specifications
 - Net Antenna Gain : 33.4 dBi
 - Noise Temp: 136 Kelvin
 - Beam width: 2.75 degrees
 - System G/T: 11.93 dB/K
 - Polarization: RHCP
- X-Band (8.2GHz) Downlink Specifications
 - Net Antenna Gain : 45.4 dBi
 - Noise Temp: 125 Kelvin
 - Beam width: 0.76 degrees
 - System G/T: 26.2 dB/K
 - Polarization: RHCP

Positioner & Pedestal Specifications

- Type 1, three-upright pedestal
- X / Y axis drive configuration giving full hemispheric coverage
- No 'cone of silence' (keyhole) at zenith
- Slew rates up to 5 degrees per second
- Pointing accuracy better than 0.1 degree
- Both axes are controlled simultaneously
- Software autotrack to maintain optimum signal strength
- Ethernet-connected pedestal enclosure for motor drives and control equipment
- Innovative platform compensates for ground movement, ensuring antenna pointing stability during freeze/thaw cycles.

Radome Specifications

- Fibreglass enclosure consisting of interconnected hexagons
- Access hatch, lightning protection and safety shut-down switch on exterior
- Interior lighting, web camera and environmental control
- Ethernet-connected pedestal enclosure for radome monitoring and control equipment

Additional Information

- Data backhaul via VPN connections over MacKenzie Valley Fibre Link
- Local and remote monitoring and control capability
- UPS power and backup generator
- Gated one-kilometer roadway and fenced site with security system and cameras

Planned for 2019

- S-band (2.1GHz) Uplink
- UHF (450MHz) Uplink and Downlink ability to switch between RHCP and LHCP Polarization



Captain Robert A. Bartlett Building
1 Morrissey Road, St. John's, NL, Canada A1B 3X5
709.864.8354 • info@c-core.ca

4043 Carling Avenue, Suite 202
Ottawa, ON, Canada K2K 2A4
613.592.7700

c-core.ca